



The GIPO B0960 Jaw crushers are suitable for the harshest usage in quarrying and also for recycling construction materials. The range of customer-specific options is unique and almost unlimited. Whether hopper wearing lining, apron conveyor feed or a coarse pre-screen: the plant is adapted to your needs.

You can choose between a conventional diesel engine, an electrical drive system or even a combined drive system. A further highlight is the ferrous metal discharge in the longitudinal direction, which has been a unique feature of GIPO plants for years.

TECHNICAL DATA

JAW CRUSHER

Crusher Inlet (W x L)	900x600mm
Gap width (mm)	40-160mm

FEED HOPPER

Volume	4m ³ *
Max feed size	200mm
Capacity	Up to 400tph
Larger capacity due to feed channel 7m ³	
Hydraulic lockable hinged walls	

FEED CHANNEL

C Channel (WxL)	880x3400mm
FDR Chanel (WXL)	810x2350mm

CONVEYORS

Crusher Discharge Conveyor

Width	1000mm
-------	--------

Feed Conveyor

Width	1200mm
Continuous loading & material distribution	
Dosing flap for controlled material flow	

Return Conveyor

Width	400mm
Can be used as side discharge conveyor	

PRE-SCREENING

Upper Deck	900x1920mm
Lower Deck	Spi 1285x880mm
Pre-Screen Conveyor	650mm



JAW CRUSHER IN USE

- | | | | |
|--------------------|----------------------------|------------------------|--------------------------------|
| 1. Feed hopper | 4. Side discharge conveyor | 7. Fixed crushing jaw | 10. Crusher discharge conveyor |
| 2. Pre-screening | 5. Jaw crusher | 8. Moving crushing jaw | |
| 3. Changeover flap | 6. Jaw crusher bearings | 9. Gap adjustment | 11. Crusher drive motor |

