



# GIPO B1370

## JAW CRUSHER



GIPO's B1370 tracked mounted, single toggle 1330 x 700 Jaw is capable of handling the toughest rock and quarrying applications with simple hydraulic gap adjustment, permits an exact setting to give you the required grading. With limited automation the jaw features simple user friendly controls and easily access components for servicing

### CRUSHER

Heavy Duty Single Toggle Jaw  
 Inlet Crusher Jaws 1330mm x 700mm  
 Gap Width 70mm to 200mm  
 Capacity 550tph

### POWER UNIT

Drive Diesel/Hydraulic  
 Type CAT C15  
 Power 433kW / 580HP  
 Rexroth hydraulic pumps & drives  
 Cooling Water-cooled

### PRE SCREEN

Independent Double Deck pre-screen  
 Remote control

### CONVEYORS

#### DISCHARGE CONVEYOR

Width 1400mm  
 Length 12000mm

#### SIDE CONVEYOR

Width 650mm  
 Length 18000mm

### FEEDING

Hopper 6m<sup>3</sup> Capacity  
 Hardox Hopper Walls  
 Feed Channel Vibrating

### FEATURES & BENEFITS

- Full hydraulic drive concept
- System widths of the conveyor elements open in the direction of material flow.
- Can be operated without additional supports and thus great mobility is guaranteed
- Water spraying system
- Remote control for feed channel
- D7 tracks
- Limited automation, easy simple to use controls
- Fwd & reverse jaw operation

### TRANSPORT DIMENSIONS

Length 18400mm  
 Width 3300mm  
 Height 3850mm  
 Weight 75000kg approx.