

C1200 CONE CRUSHER



The track mounted 41 tonne C1200 Cone Crusher is designed to produce high quality cubical aggregates. Featuring CAT C9.3 engine for added power, ground clearance kit with easy access for maintenance & servicing, applications and more...

CONE CRUSHER

High performance Cone Crusher
Crusher Cone C200-900mm
Fully Hydraulic for clamping, adjustment & cleaning
Cone setting: 10mm - 38mm
Crusher level sensor
Zero set
Liners available Fine, Med, Coarse, extra coarse

POWER UNIT

Drive Diesel/Hydraulic
Type CAT C9.3
6 Cylinder Engine
Power 310kW
Engine Speed 2200rpm
Fuel Tank Capacity 640L
Hyd Tank Capacity 600L

FEEDING

Hopper 5/7m³ Capacity
Twin shaft geared design with hydraulic drive
Feeder Integrated Hydraulic Linear Plate
Length 5500mm
Width 2500mm
Variable Speed 0-960rpm
Remote Control Start/Stop

MAIN CONVEYOR

Width 1200mm
Discharge height 3510mm

STANDARD INCLUSIONS

- Multi-machine logic controller
- Ground clearance kit
- Mine spec hose sheath
- Fixed wear resistant feed hopper
- Metal detector
- Medium bowl liner -18% manganese
- Feed conveyor 1200mm wide
- Product Conveyor 1200mm wide
- Hot climate oils
- Nip point guarding
- Remote greasing
- Engine start delay & siren
- Warning siren to alert tracking
- Engine emergency stops
- Dust suppression sprays and manifold
- Radio remote control unit
- Dual drive forward conveyor

DIMENSIONS

	Transport	Working
Length	15400mm	14600mm
Width	3200mm	3200mm
Height	3800mm	4400mm
Weight (approx.)	41,000kg	